



cbr600rr4

Produktnummer: cbr600rr

CBR600RR

Nyhet!

kr 206.990,00

Be om tilbud

- **Beskrivelse**

Ny lavere pris! satt ned fra 224990,-

Honda CBR600RR

New Model: *Honda's middleweight supersport jewel returns to Europe, destined for road and track action. Its inline four-cylinder, 16V DOHC engine produces 89kW @ 14,250rpm and features an assist/slipper clutch and standard fit quickshifter. Throttle By Wire control - derived from the RC213V-S - along with addition of a Bosch 6-axis IMU delivers 3 default riding modes, plus two custom User modes for adjustment of Engine Power, Engine Braking, Wheelie Control and 9-level HSTC. Cornering ABS and Rear Lift Control are also part of the package. The chassis comprises an aluminium twin-spar frame, aluminium swingarm, Honda Electronic Steering Damper, 41mm Showa Big Piston USD forks and Unit Pro-Link*

Showa rear shock. Dual, radial-mount four-piston front calipers work 310mm floating discs. Designed to deliver best-in-class aerodynamic performance, the aggressive styling includes

downforce-generating front winglets. A full colour TFT screen completes the specification. An HRC Race Kit will also be an option, for circuit use only.

ENGINE	
Type	Liquid cooled 16-valve DOHC, inline-4
Engine Displacement (cm ³)	599cc
No. of Valves per Cylinder	4
Bore ´ Stroke (mm)	67mm x 42.5mm
Compression Ratio	12.2:1
Max. Power Output	89kW @ 14,250rpm
Max. Torque	63Nm @ 11,500rpm
Noise Level	Lurban - 74dB, Lwot - 77dB
Oil Capacity	3.4L
FUEL SYSTEM	
Carburation	PGM-FI
Fuel Tank Capacity	18L

C02 Emissions WMTC	128 g/km
Fuel Consumption	18.2km/L (5.5L/100km)
ELECTRICAL SYSTEM	
Starter	Electric
Battery Capacity	12-9.1Ah YTZ10S
DRIVETRAIN	
Clutch Type	Wet, multiplate hydraulic clutch
Transmission Type	Manual 6-speed
Final Drive	Chain
FRAME	
Type	Aluminium twin tube composite twin spar
CHASSIS	
Dimensions (L x W x H)	2,030mm x 685mm x 1140mm
Wheelbase	1,370mm
Caster Angle	24 ° 06'

Trail	100mm
Seat Height	820mm
Ground Clearance	125mm
Kerb Weight	193kg
SUSPENSION	
Type Front	Fully adjustable Showa 41mm Big Piston USD, 120mm stroke.
Type Rear	Fully adjustable Showa rear shock operating through Unit Pro-Link. 128mm axle travel
WHEELS	
Rim Size Front	17M/CxMT3.50
Rim Size Rear	17M/CxMT5.50
Tyres Front	120/70ZR17M/C DUNLOP Roadsports2
Tyres Rear	180/55ZR17M/C DUNLOP Roadsports2
BRAKES	
ABS System Type	2 channel

Front	310mm floating discs with radial-mount 4-piston caliper
Rear	220mm disc with single piston caliper
INSTRUMENTS & ELECTRICS	
Instruments	TFT-LCD
Security System	HISS
Headlight	LED
Taillight	LED
Quickshifter	Yes

NB: Leveringsomkostninger (montering/klargjøring/registrering) kr 4000,- kommer i tillegg til annonsert pris.

Vi tar forbehold om prisendringer og feil i beskrivelsen.

- Tilbehør

Tilbehør

ob101

Oxford ryggskinne

CE level two

- kr 499,00

mig

Ixon Mig

Bestselger!

- kr 599,00

Info

bf41

Tanklock feste

Honda 5 hull

- kr 299,00

MC-butikken AS

Industrigata 12
5537 HAUGESUND
NORGE

post@mcbutikken.com